Where do carrots grow?

Object.assign() and classes



```
class Carrot {
   name = "carrot"
   grow() {
      return `${this.name}s grow in the ground`
   }
}
```

```
class Apple {
   name = "apple"
   grow() {
      return `${this.name}s grow on trees`
   }
}

class Carrot {
   name = "carrot"
   grow() {
      return `${this.name}s grow in the ground`
   }
}
```

```
class Apple {
    name = "apple"
    grow() {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow() {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

console.log(carrot.grow())
```

```
class Apple {
    name = "apple"
    grow() {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow() {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

console.log(carrot.grow())
```

carrots grow in the ground



```
class Apple {
   name = "apple"
   grow() {
      return `${this.name}s grow on trees`
   }
}

class Carrot {
   name = "carrot"
   grow() {
      return `${this.name}s grow in the ground`
   }
}
```

```
class Apple {
    name = "apple"
    grow() {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow() {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

console.log(carrot.grow())
```

```
class Apple {
   name = "apple"
   grow() {
      return `${this.name}s grow on trees`
   }
}

class Carrot {
   name = "carrot"
   grow() {
      return `${this.name}s grow in the ground`
   }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)
console.log(carrot.grow())
```

```
class Apple {
    name = "apple"
    grow() {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow() {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)

console.log(carrot.grow())
```

```
class Apple {
    name = "apple"
    grow() {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow() {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)

console.log(carrot.grow())
```

```
class Apple {
    name = "apple"
    grow() {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow() {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)
console.log(carrot.grow())
```

```
class Apple {
    name = "apple"
    grow() {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow() {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)
console.log(carrot.grow())
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)

console.log(carrot.grow())
```

```
class Apple {
    name = "apple"
    grow() {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow() {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)
console.log(carrot.grow())
```

```
class Apple {
   name = "apple"
   grow = () => {
      return `${this.name}s grow on trees`
   }
}

class Carrot {
   name = "carrot"
   grow = () => {
      return `${this.name}s grow in the ground`
   }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)
console.log(carrot.grow())
```

```
class Apple {
    name = "apple"
    grow = () => {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow = () => {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)

console.log(carrot.grow())
```

```
class Apple {
    name = "apple"
    grow = () => {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow = () => {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)

console.log(carrot.grow())
```

```
class Apple {
    name = "apple"
    grow = () => {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow = () => {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)
console.log(carrot.grow())
```

```
class Apple {
   name = "apple"
   grow = () => {
      return `${this.name}s grow on trees`
   }
}

class Carrot {
   name = "carrot"
   grow = () => {
      return `${this.name}s grow in the ground`
   }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)
console.log(carrot.grow())
```

```
class Apple {
   name = "apple"
   grow() {
      return `${this.name}s grow on trees`
   }
}

class Carrot {
   name = "carrot"
   grow = () => {
      return `${this.name}s grow in the ground`
   }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)
console.log(carrot.grow())
```

```
class Apple {
    name = "apple"
    grow() {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow = () => {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)
console.log(carrot.grow())
```

```
class Apple {
    name = "apple"
    grow() {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow = () => {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)
console.log(carrot.grow())
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)
console.log(carrot.grow())
```

```
class Apple {
    name = "apple"
    grow = () => {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow() {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)

console.log(carrot.grow())
```

```
class Apple {
    name = "apple"
    grow = () => {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow() {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)
console.log(carrot.grow())
```

```
class Apple {
    name = "apple"
    grow = () => {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow() {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)
console.log(carrot.grow())
```

```
class Apple {
    name = "apple"
    grow = () => {
        return `${this.name}s grow on trees`
    }
}

class Carrot {
    name = "carrot"
    grow() {
        return `${this.name}s grow in the ground`
    }
}
```

```
const apple = new Apple()
const carrot = new Carrot()

Object.assign(carrot, apple)
console.log(carrot.grow())
```

```
Apple GdocBase
Carrot GdocAuthor
grow() _enrichSubclassContent()
```

The target of the assign is irrelevant

- if fn is enumerable, it will always take over
- if fn is non enumerable, it will never be used*

When in doubt, use class methods

- override behaviour is less surprising
- better performance